




ezoBord Sample Colors

3/8" (9mm)




PB09 - PURE BLACK



CG06 - CHARCOAL GRAY



ES07 - EBONY SLATE



SG04 - SILVER GRAY




CW04 - CLASSIC WHITE



LB01 - LIGHT BEIGE



SD18 - SUNNY DAYS



TO24 - TIGER ORANGE




RR28 - RUBY RED



MN12 - MIDNIGHT NAVY




PI14 - POLAR ICE




GA41 - GREEN APPLE



DG34 - DARK GRAY



DS10 - DESERT SAND



DP30 - DEEP PURPLE



EB50 - EVENING BLUE



VC97 - VANILLA CREAM



SP99 - SUNSET PINK



AB32 - AEGEAN BLUE

COMPOSITION

100% PET (min. %50 recycled content)

THICKNESS

3/8" (9mm) standard.
Other thicknesses available; minimum
order quantities apply

WEIGHT

8.5lbs (±5%) Per sheet

HARDNESS

60-65 (Shore C)

DIMENSIONS

48" (1219mm) x 108 3/16" (2748mm)
(±1mm) = Full Sheet

FIRE TESTING

- North America:
 - ASTM E-84 Class A*
 - CAN ULC S102-10
- Europe and UK:
 - EN13501-1: 2007

ENVIRONMENT

Made of polyester fiber, min. 50% of
which comes from recycled water
bottles which contributes to LEED MR
Credit & BREEAM Health & Wellbeing,
Materials points due to recycled
content, acoustic performance, & low
emitting materials. No VOC's: CDPH
v1.2 and REACH SVHC Compliant.

ACOUSTICS

Refer to ASTM C423 test charts for
specific absorption coefficients. NRC
0.75 (subject to mounting conditions)

APPLICATIONS

Wall and ceiling, tack-boards,
visual & acoustical privacy barriers,
acoustic canopies, & other custom
applications.

PRODUCT VARIANCES

Variation in fiber mix & colour may
occur. All products will be supplied
within commercial tolerances.

GENERAL

Tackable, impact resistant, bacteria
resistant, moisture resistant,
installation friendly.

CUSTOM ORDERS

Custom design options include CNC
cutting for virtually any shape & printing.

**Upon request, 3/8" (9mm) sheet
material is treated with USA origin post-
production flame retardant to Class A
surface burning characteristics. Post
sheet production FR treatment does
not contain any Red List Restricted
Chemicals & complies with California
Proposition 65. Contact customer service
for technical information, test data &
safety data sheets for flame retardant.*